

Patent Application  
Chapin & Huang/BWC  
December 1, 2000

Attorney Docket No.: CIS00-3681

5

-1-

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as Express Mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on

Date: December 1, 2000 Express Mail Label No.: EF208416937US

Signature: *Barry W. Chapin*

Typed or Printed Name: Barry W. Chapin, Esq., Reg. No. 39,934

Inventors: Daniel A. Nagel and Chad A. Reese

10

Attorney Docket No.: CIS00-3681

## METHODS AND APPARATUS FOR EXCHANGING INFORMATION BETWEEN BROWSER PAGES

15

### FIELD OF THE INVENTION

20

The present invention generally relates to mechanisms and techniques for exchanging information between pages such as browser pages in a browser, and more particularly, to systems and techniques which allow variables and state information to be captured and transmitted from one browser page to another.

### BACKGROUND OF THE INVENTION

25

Computer networks such as the Internet provide a variety of different mechanisms that allow a person to perform communications and data processing tasks. One such mechanism is called the World Wide Web or simply "the web." Generally, the World Wide Web comprises a collection of inter-operating client and server software applications which use a suite of data communications protocols to communicate with each other. A typical conventional client software application is a web browser and operates on a client computer system such as a personal computer or workstation under

control of a user. The user can operate the web browser to access web pages that conventional server software operating on a server computer system serves to the web browser over a computer network such as the Internet. In some circumstances, a web browser can access or load web pages, documents, files or other information other than those provided by server software. By way of example, a user of a computer can operate a web browser to access web pages or other documents stored locally within a file system (e.g., on a disk) in that user's computer, without the web browser having to interact with a web server in a remote location over a computer network.

A conventional web page may include information formatted in a markup language such as the hypertext markup language (HTML). The web browser can load and interpret an HTML formatted web page in order to display or present to the user any text, graphics, audio, video or other data contained within, or referenced by, the web page. A typical web page can include one or more hypertext links, also referred to simply as "links" or Uniform Resource Locators (URLs) which can reference information not specifically contained within the web page.

A link or URL within a web page can serve a variety of purposes. Generally, however, links operate as location identifiers to reference other data or information not specifically contained within the web page that contains the link. Some links are called embedded links that reference data (e.g., an audio file or a graphic image) that is to be loaded into the web browser in conjunction with the web page, when a web browser accesses the web page containing the embedded link. For instance, an HTML instruction within a web page may contain an embedded link to a graphic file. Many different web pages may each contain an embedded link to the same graphic file. When a web browser loads any one of such web pages, the web browser, during interpretation of the HTML instructions within the web page, detects the embedded link and proceeds to reference and load the graphic image contained in the graphic file referenced by that embedded link. In this manner, the embedded link serves as a location identifier for the graphic image and causes the graphic image data to be incorporated into the view of the web page that the web browser presents to the user.

Other links within a web page may provide navigation functionality for the user of the web browser. For instance, a link within a first web page may reference a second web page. Such a link may not be an embedded link in this sense that a web browser that interprets such a link within a web page may not immediately reference the data or other information (i.e., the second web page in this example) referred to by the link. Instead, the web browser can present, render or otherwise display the link to the user along with the rest of the web page contents. A typical web browser implementation can associate a link to a text phrase, graphic or icon associated with the link. A user of the web browser that invokes the link, for example, via a click of a mouse on the text, graphic or icon associated with the link, causes the web browser to navigate (i.e., to load and obtain) the data referenced by that link. In the instant example then, a user may select the underlined link referencing the second web page, which causes the browser to invoke access to the second web page for display to the user. In this manner, a link can be used to cause a web browser to navigate between web pages. Web browsers often provide other web page navigation features such as BACK and FORWARD buttons that cause the browser to load a next or a previous web page, based on a history of web page location identifiers (e.g., URLs) of web pages that a user has visited (i.e., that the browser has displayed for viewing by the user).

Modern web browser software applications also typically include an ability to process web pages that include logic or programming instructions that can perform complex tasks within the processing environment of a web page provided by the web browser. As an example, most web browser software applications come bundled with (i.e., include an interface to) a Java or JavaScript interpreter (also known as a Java virtual machine or JVM) that allows the web browser to process web pages that include JavaScript. JavaScript is a scripting language that provides functionality much like a programming language within the environment of a web page. For instance, a single web page can include JavaScript statements (i.e., JavaScript commands and/or logic instructions) that can perform complex calculations, data manipulations, graphics processing or other tasks. A web browser typically causes such script processing to occur with the web page containing the JavaScript is loaded into web browser for presentation

to a user. Other conventional scripting languages exist as well which operate within the context of a web page loaded into a web browser. An example of another of such scripting languages for use in web pages is VBScript, produced by Microsoft Corporation of Redmond, Washington.

- 5           Typical examples of conventional web browser software applications are Netscape Navigator manufactured by Netscape Corporation, of Mountain View, California, and Internet Explorer manufactured by Microsoft Corporation.

## SUMMARY OF THE INVENTION

- 10           The operation of conventional web browser software applications that operate with conventional web pages, that may include conventional script logic instructions such as JavaScript, suffer from a number of drawbacks. In particular, if a conventional web page includes JavaScript or another scripting/programming-type language in the form of a routine, function or set of instructions (e.g., JavaScript code), such script code has
- 15           limited ability to interoperate with other script code, functions or routines that may exist within other web pages. This is primarily because a typical conventional web browser treats a single web page which is loaded into the web browser for viewing by the user as a self-contained environment with respect to any script code that may be contained and operated upon (e.g., interpreted) by the web browser within that web page.

- 20           Thus, when a browser loads one web page for viewing by a user, other web pages that the browser may have previously loaded or that will be loaded in the future are inaccessible (i.e., are not loaded into memory at all) with respect to the scripting code or logic within the page currently loaded into the browser. That is, script code existing in a web page cannot directly exchange data with other script code in other web pages that are
- 25           not currently being viewed by the user of the browser.

- Still further, conventional JavaScript or other such scripting languages were not developed with the intent of writing entire software applications in the scripting language in a web page. Rather, scripting languages such as JavaScript are intended to provide basic or limited processing functionality in a single web page environment within a
- 30           browser for such tasks as manipulating graphic images, obtaining user supplied data, or

other tasks related to the web page in which the scripting instructions are included. As such, conventional scripting instructions contained in a web page do not include an ability to maintain state information between a portion of script code in one web page and another portion of script code in another web page. Conventional web page scripting languages thus do not have direct access to computer system memory or registers in a processor of the computer system, nor do they contain the ability to create data structures such as stacks, heaps or other memory resident storage locations for use in storing data or scripting language state information as multiple web pages are loaded, viewed and then unloaded within a browser.

The present invention is based in part on these observations and provides mechanisms and techniques that significantly overcome such limitations. In particular, the system of the invention includes method embodiments to perform techniques of the invention. Once such method embodiments operates in a browser, and includes a method for transferring information between logic entities in browser pages. Logic entities are any type of processing logic or instructions can be executed, run, interpreted or otherwise performed within a web page environment with a browser in a computer system.

In particular, one method of the invention comprises the step of defining a data element having a value for use by a first application logic entity in a first browser page. The first application logic entity can be any type of performable instructions, routine, function, procedure or other type of processing that the browser can perform all displaying a browser page. In a preferred embodiment, application logic entities contained processing or script code (e.g., JavaScript) that carries out tasks related to software application which uses the invention to pass state information between application logic entities. The data element maybe, for example, a JavaScript variable and the value may be any data or information assigned as the contents of the variable by the step of defining. The method generates a browser page identifier for a second browser page. The browser page identifier maybe a URL or other page identification mechanism. The browser page identifier includes the value for the data element. In a preferred embodiment, the value for the data element (of which there may be more than one) is appended at the end of the browser page identifier is a character delineated string

of figures. The method also includes the step of invoking access to a second browser page using the browser page identifier. The second browser page can include a second application logic entity. The method then retrieves the value of the data element from the browser page identifier for use by the second application logic entity. In this manner, the invention allows browser pages to exchange state information.

According to another method embodiment of the invention, the step of defining a data element includes the steps of declaring a data element for use by a first application logic entity and providing a value for the data element. In a related embodiment, the step of providing a value for the data element comprises the step of retrieving the value for the data element from a browser page identifier identifying the first browser page. Using these techniques, the method embodiments of the invention can define or declare data elements for use by logic entities with a browser page. In the related embodiment, values for data elements are retrieved from a browser page identifier identifying the browser page in which the logic entities exist.

In another embodiment of the invention, the step of retrieving a value of the data element from a browser page identifier identifying the first browser page includes the steps of parsing the browser page identifier to retrieve a value for a data element from the browser page identifier and assigning the value to the data element that corresponds to the value parsed from the browser page identifier. Using this technique, the invention can retrieve values for data elements for a browser page identifier which may be, for example, a URL of the page in which the logic entities that implement the method of the invention operate. Also according to this method embodiment, the method repeats the steps of parsing and assigning for each value contained in the browser page identifier such that all data elements containing a value within the browser page identifier receive an assignment of their respective value parsed from the browser page identifier. As such, a browser page identifier is created according to the invention to include values for many different data elements that can be passed between browser pages.

In yet another embodiment, the step of generating a browser page identifier includes the steps of extracting a value for each data element shared between the first application logic entity and the second application logic entity to create a value array.

The value array maybe, for example, a character delineated string of data element values. The method embodiment also includes the steps of obtaining a page designator for the second browser page and appending the value array containing the values for each data element to the page designator for the second browser page to form the browser page identifier. Using this technique, this method embodiment can dynamically and automatically generate or create a browser page identifier such as a URL which identifies a page, for instance, which the user desires to navigate to and which also contains data element values for data elements used by logic entities within the page that the user is navigating from.

10 In a further embodiment, the browser page identifier is a uniform resource locator that is dynamically generated via the steps of extracting, obtaining and appending and that contains the value of the data element shared by the first application logic entity and the second application logic entity. Thus the uniform resource locator includes state information for application logic entities that in this embodiment comprises values of  
15 data elements used by those application logic entities.

Another embodiment of the invention includes the step of detecting a navigation command to navigate to the second browser page. Also in this embodiment, the steps of generating and invoking are performed in response to the step of detecting the navigation command to navigate to the second browser page, such that the browser page identifier produced in response to the step of detecting the navigation command includes a value  
20 for the data element that is created by the first application logic entity and is passed to the second application logic entity via the browser page identifier. Accordingly, the navigation command that a browser receives, for instance, from a user of the browser can trade the operation of the invention to pass state information from a current browser page that the user is viewing to a browser page to which the user attempts to navigate.  
25

In yet another embodiment, the steps of generating and invoking are performed by a state sender logic entity that operates within the browser in a computer system and the step of retrieving is performed by a state retrieval logic entity that also operates in the browser. The state sender logic entity and state retrieval logic entity are logic entities  
30 incorporated into the first browser page and second browser page which interoperate to

transfer values of data elements shared by the first application logic entity and the second application logic entity between the first browser page and the second browser page via incorporation of such values of data elements into browser page identifiers. An example of a state sender logic entity is the `send_query_string` JavaScript function or routine  
5 provided within the example implementation of the invention shown in APPENDIX A. An example of a state retrieval logic entity is the `get_variables` JavaScript function provided within the example implementation shown in APPENDIX A.

In another embodiment, the first application logic entity and the second application logic entity collectively form an application. Also in this embodiment, the  
10 values of data elements shared by the first application logic entity and the second application logic entity collectively form state information that the state sender logic entity and the state retrieval logic entity can pass between the first browser page and second browser page via browser page identifiers for use by the application. This allows the state sender logic entity and a state retrieval logic entity to interoperate with each  
15 other between browser pages to exchange state information for use, for example, by application logic entities also included within those browser pages.

Other embodiments of the invention include computer systems configured to perform all of the method embodiments summarized above and explained herein as the invention. In particular, such computer system embodiments include a processor, a  
20 memory system and an interconnection mechanism coupling the processor and the memory system. The memory system is encoded with an browser application that, when performed on the processor, forms a browser that operates to cause the computer system to performing all of the operations of the method embodiments and operations of the invention. That is, the invention includes computer systems configured to perform all of  
25 the method operations in embodiments disclosed herein.

Generally, embodiments of the invention can perform all of the methods disclosed herein via software control, or via hardware and/or software configured to perform those methods and the techniques.

Other embodiments of the invention that are disclosed herein include software  
30 programs to perform the methods and operations summarized above and disclosed in



detail below. More particularly, a computer program product is disclosed which has a computer-readable medium including computer program logic encoded thereon to provide the methods for transferring information between logic entities in browser pages according to this invention. The computer program logic, when executed on at least one processor within a computing system, causes the processor to perform the operations (e.g., the method embodiments and operations summarized above, and described in detail later) indicated herein. This arrangement of the invention may be provided as software on a computer readable medium such as an optical medium (e.g., CD-ROM), floppy or hard disk or other such medium such as firmware in one or more ROM or RAM or PROM chips or as an Application Specific Integrated Circuit (ASIC). The software, firmware or other such configurations can be installed onto a computer system to cause the computer system to perform the techniques explained herein as the invention.

It is to be understood that the system of the invention can be embodied strictly as a software program, as software and hardware, or as hardware alone. Is also to be understood that the event processing techniques and mechanisms of this invention typically perform (e.g., execute, run, or are otherwise operated) on computer systems coupled to a computer network, though this is not required for the invention. Is also to be understood computer systems configured according to the invention include a browser process such as a web browser and a preferred embodiment of the invention is implemented within a state retrieval logic entity which may be, for example, a JavaScript routine and within a state sender logic entity which may also be, for example, a JavaScript routine, each of which may be included for within browser pages that the web browser may load and process accordingly.

The invention may be embodied in systems, software and/or hardware products designed, developed and/or manufactured by Cisco Systems, Inc. of San Jose, California.

## BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the invention will be apparent from the following more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters

refer to the same parts throughout the different views. The drawings are not necessarily to scale, with emphasis instead being placed upon illustrating the embodiments, principles and concepts of the invention.

Figure 1 illustrates a computing system environment that is suitable for use in  
5 describing example operations of embodiments of the invention.

Figure 2 shows a flow chart of processing steps performed by a browser operating according to embodiments of the invention.

Figure 3 illustrates details of first and second browser pages which incorporate and use the system of the invention in a browser.

10 Figure 4 is a flow chart of processing steps as performed by a state sender logic entity configured to operate according to embodiments of the invention within a browser.

Figure 5 is a flow chart of processing steps as performed by a state retrieval logic entity configured to operate according to embodiments of the invention within a browser.

## 15 DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The present invention provides techniques and mechanisms that enable the transfer of information between logic entities (e.g., groups of processing logic instructions) that operate within different browser pages. As an example, a web browser can load a first browser page (e.g., web page) containing one or more logic entities  
20 configured in accordance with invention. The logic entities may be, for example, JavaScript routines. One such JavaScript routine can exist within a first browser page and can define one or more data elements such as JavaScript variables. The JavaScript routine can retrieve values for the data elements from a browser page identifier associated with the first browser page. The browser page identifier may be, for example, a URL of  
25 the first browser page that includes state information appended to the end of the URL that contains the values for the data elements to be accessed by the JavaScript routine. The JavaScript routine can retrieve the values for the data elements, for example, by parsing the URL to extract the values for the data elements from the state information appended to the end of the URL.

Another logic entity (e.g., another JavaScript routine) configured in accordance with the invention and incorporated into a browser page can detect the invocation of browser processing to access another browser page. As an example, a JavaScript routine operating as such a logic entity can be activated when the user of the web browser selects (e.g., clicks on) a link to navigate to another browser page. In response to this, the JavaScript routine can dynamically and automatically generate a browser page identifier, such as a URL, for a second browser page (i.e., the browser page to which the user desires to navigate to next from the current page), from within the first browser page (i.e., by the JavaScript activated in response to the navigation command in the page that the user is currently viewing). As such, the browser page identifier (e.g., a URL) is dynamically and automatically generated.

During the generation of the browser page identifier, the JavaScript routine of the invention performing this process can extract a value for each data element that is required to be passed to another logic entity that will operate within the second browser page. The JavaScript routine can then append the values for the data elements (e.g., as a string in which each value is delineated with a predetermined character such as "&") onto a page designator for the second browser page, in order to dynamically create the URL for the second browser page that contains the values of data elements from the first browser page. The JavaScript routine can then invoke access to the second browser page using the browser page identifier which was just dynamically created.

In this manner, a URL created according to the invention can contain values for data elements from the first browser page which are passed to an awaiting logic entity within the second browser page for extraction from the URL of the second browser page. In this manner, logic entities such as JavaScript routines contained within different browser pages can pass state information such as values for data elements using browser page identifier's which caused navigation of the browser from one browser page to another.

Figure 1 illustrates a computer system 100 configured in accordance with an example embodiment of the invention. The computer system 100 includes an interconnection mechanism 105 which couples a processor 110, an input-output interface

120, and a memory system 130. The memory system 140 is encoded with logic instructions (e.g., software code) that form a browser application 135 which can access a plurality of browser pages 150-1 through 150-N (collectively browser pages 150). The browser pages 150 may be HTML encoded web pages, for example. Accessible to the  
5 browser application 135 in the memory system 130 are state logic entities 180 configured in accordance with the invention. In one embodiment, the state logic entities 180, which will be explained in more detail shortly, are script routines comprised of JavaScript. The processor 110 can execute, run, interpret, or otherwise perform the logic instructions of the browser application 135 and any associated browser pages 150 and/or state logic  
10 entities 180 to form the browser 140. In other words, the browser 140 represents the execution or other operation of logic instructions that form the browser application 135, browser pages 150, and state logic entities 180 on or within the processor 110 in the computer system 100.

Each browser page 150 may include one or more application logic entities 170-1  
15 through 170-P which can collectively operate between browser pages 150, using the invention, to form a complete software application as will be explained. The application logic entities 170 may be, for example, JavaScript or VBScript routines, Java applets or other operations or functions embedded within the browser pages 150 to perform any required functionality as intended by a developer (e.g., a person) who designs and  
20 develops the collection of browser pages 150. As an example, the application logic entities 170 may perform graphics and/or data processing that produces state information 155 such as values for data elements (e.g., JavaScript variables, not specifically shown) within their respective browser pages 150.

The computer system 100 illustrated in Figure 1 is suitable for use in explaining  
25 example operations of the system of the invention. Generally, the state logic entities 180 provide the required functionality of the invention that allows a browser page 150 such as browser page 150-1 to operate (e.g., to execute, run, interpret or otherwise perform) the application logic entity 170-1 within the browser 140 to produce state information 155 including data elements (not specifically shown) such as variables that can have  
30 associated values. When an application logic entity such as 170-1 has completed its

processing of the state information 155 (i.e., has used, accessed, or otherwise processed or manipulated data elements that comprised the state information 155), the browser page 150 (150-1 in this particular example) can access and operate the state logic entities 180 configured in accordance with the invention to pass the state information 155 between the browser page 150 (between browser page 150-1 and 150-2 in the illustrated example) via the use of a browser page identifier 160 (only one example of this operation shown in Figure 1). As will be explained further, a browser page identifier 160 may be, for example, a URL of a browser page 150 that, in this invention, includes state information 155 contained within the URL.

Figure 2 illustrates a flow chart of processing steps as performed by the browser 140 including (i.e., operating in conjunction with) one or more associated browser pages 150 and state logic entities 180 configured in accordance with embodiments of the invention.

In step 200, the browser 140 defines a data element having a value for use by a first application logic entity in a first browser page. By way of example, in step 200, the browser 140 may access (i.e., may invoke the processing of) a state logic entity 180 such as a JavaScript routine which defines (e.g., declares) one or more JavaScript variables including associated values to serve as data elements for use by the application logic entity 170-1 within the browser page 150-1.

Next, in step 201, the browser 140 generates, via the processing of a state logic entity 180 in this embodiment, a browser page identifier 160 for a second browser page such as browser page 150-2. The browser page identifier 160 includes the value for the data element as defined in step 200. As noted above, in a preferred embodiment, the browser page identifier 160 generated by the invention in step 201 is a URL of a browser page 150 (e.g., for browser page 150-2, which may be a web page in the example in Figure 1) which includes any values for data elements defined within the state information 155 as used by an application logic entity 170 (e.g., 170-1 in the example in Figure 1). The state logic entity 180 performing step 201 within the browser 140 may append the values of data elements to the end of the browser page identifier 160, for example, as a character delineated string of values. Thus, after processing step 201, the

browser page identifier 160 identifies another browser page 150 (i.e., preferably other than the current page 150-1) and also includes a data element value (one or more, only one mentioned here) for a data element(s) from the current page. As will be explained, such data element values can be accessed or extracted from the browser page identifier 160 for use by logic entities 170 in the other browser page (e.g., for use by logic entity 170-2 in page 150-2) via this invention.

In step 202, the system of the invention operating within the browser 140 invokes access to a second browser page (150-2 in the instant example) using the browser page identifier 160 that was generated in step 201. The second browser page (e.g., 150-2) includes a second application logic entity 170 (specifically, 170-2 in the illustrated example). In other words, in step 202, the browser 140, via use, in this embodiment, of a state logic entity 180 configured according to the invention, obtains and loads the second browser page based on the URL created in step 201.

In step 203, the browser 140 equipped with the system of the invention, which now contains (i.e., has loaded and is in the process of rendering) the second browser page 150 (specifically, 150-2 in this example), uses a state logic entity 180 of the invention to retrieve the value of the data element from the browser page identifier 160 for use by the second application logic entity 170 (specifically, 170-2 in this example). In a specific embodiment as will be explained shortly, in step 203, the browser 140 loads the second browser page 150 (e.g., 150-2) referenced by the browser page identifier 160. The second browser page 150 (e.g., 150-2 in Figure 1) includes a call to a state logic entity 180 that parses the browser page identifier 160 (e.g., parses the URL) of the second browser page 150 in order to extract a value for each data element within the state information 155, as required for use by any application logic entities 170 that exist within the second browser page 150. In other words, in step 203, once the browser 140 has obtained and loaded the second browser page 150-2 for viewing by a user, the state logic entity 180 of the invention accesses the URL used to obtain that page to extract any required data element (i.e., variable) values which were appended to the end of the URL, for example as a character delineated string, during the generation of that URL in step 201 within the first browser page 150-1.

In this manner, the system of the invention allows browser pages 150 to incorporate functionality provided by the state logic entities 180 of the system of the invention to gather, collect or otherwise bundle state information including data element values used by application logic entities (e.g., JavaScript) in one browser page and include or append such collected or bundled state information onto a dynamically generated URL for another browser page. The state logic entities 180 can then invoke the URL generated in this manner in order to cause the browser 140 to load the other browser page. The other browser page can then use the state logic entities 180 of the system of the invention to obtain the URL and to extract or parse the values from the URL, as appended to the URL by the operation of the state logic entities in the first browser page.

Figure 3 illustrates an example embodiment and functionality of the invention in more detail. In this example, the contents of two browser pages 150-1 and 150-2 are illustrated to show how the invention operates within the context of different browser pages to pass state information from one browser page to another for use by logic entities with those browser pages.

Each browser page 150-1 and 150-2 includes a page designator 165 shown in parentheses at the top of each browser page. For example, the page designator 165-1 for the first browser page 150-1 is "HTTP://COMPUTER/PAGE1." The page designator 165 for a browser page 150 identifies the location of the browser page (i.e., what server, network location, disk drive, file system location, etc. where the page resides in storage), which in this example, is within the computer system 100. As will be explained, the system of the invention uses a page designator 165 for a browser page 150 to create a browser page identifier 160 configured in accordance with the invention.

The first browser page 150-1 includes a first application logic entity 170-1, as well as a state retrieval logic entity 180-1 and a state sender logic entity 180-2 (collectively state logic entities 180). The second browser page 150-2 includes a second application logic entity 170-2, as well as the state retrieval logic entity 180-1 and the state sender logic entity 180-2. In a preferred embodiment of the invention, the state retrieval logic entity 180-1 and the state sender logic entity 180-2 are script routines such as JavaScript functions which provide the functionality of the invention as needed to the

first and second browser pages 150-1, 150-2. Each browser page 150-1 and 150-2 may, for example, obtain access to the state retrieval logic entity 180-1 and the state sender logic entity 180-2 via incorporating a function call to each logic entity 180. In one embodiment, while not specifically shown, each browser page 150 can contain an

5 “include” statement which includes a file or library containing the logic instructions of each state logic entity 180-1, 180-2. By way of an example in which the state logic entities 180-1 and 180-2 are comprised of JavaScript, each browser page 150-1 and 150-2 may contain an HTML statement (not specifically shown in the example in Figure 3) such as:

10

```
<script language = “JavaScript” src = “ics7750.js”>
```

where a file having a filename “ics7750.js” is a JavaScript file accessible by the browser 140 within the computer system 100. The file “ics7750.js” contains the definitions (i.e.,

15 contains the JavaScript code, statements, function definitions, logic instructions, etc.) for the state retrieval logic entity 180-1 and the state sender logic entity 180-2. For more details on such an example embodiment of the invention, the reader is referred to APPENDIX A below which includes JavaScript code from the file ics7750.js and also includes two example web pages (HTML pages) which include the file ics 7750.js via the

20 above command and which include calls to functions in a Javascript code file.

APPENDIX A is an example only and embodiments of the invention are not limited as such.

The first and second application logic entities 170-1, 170-2 include any required functionality and utilize any required data element which are up to the discretion of the

25 developer of each browser page 150. In the example illustrated in Figure 3, the application logic entities 170 utilize data elements 175 and 176. For example, within the first application logic entity 170-1, the data element 175-1 “DATA\_ELEMENT1” happens to be a string data element that is assigned a value “ABC,” referenced in the figure as 178-1. The data element 176-1 “DATA\_ELEMENT2” happens to be a

30 numerical data element that is assigned a value “123,” referenced as 178-2.



In a preferred embodiment of the invention, the application logic entities 170 collectively interoperate to exchange the values 178 of data elements (e.g., the values assigned to data elements 175, 176) as state information 155 (such an exchange provided by the system of the invention) to provide a complete software application that operates over a series or collection of multiple browser pages 150. In other words, using the system of the invention to exchange state information 155 (e.g., data element values 178) between different browser pages 150, the browser pages 150 can include or provide application logic entities 170 which can collectively interoperate to create or form an entire software application.

An example operation of the system of the invention will now be provided with respect to Figure 3 and the flow charts of processing steps shown in Figures 4 and 5. The flow chart of processing steps shown in Figure 4 shows details of processing operations performed by the state sender logic entity 180-2, while the flow chart of processing steps shown in Figure 5 shows details of processing operations performed by the state sender logic entity 180-1.

Assume for purposes of this example that the browser 140 (Figure 1) has already loaded the first browser page 150-1. The first browser page 150-1 may be the start of an application for by logic entities distributed in multiple browser pages 150-1 through 150-N. While the first browser page 150-1 is being viewed by a user controlling the browser 140, the first application logic entity 170-1, which in this example comprises one or more VBScript, JavaScript or other script routines, functions, instructions or the like, processes the data elements 175 and 176 in some manner, such as assigning their respective values 178 ("ABC" and "123") as shown in Figure 3 and as explained above. Note that only two data elements are shown in this example. There may be any number of such data element variables declared for use in a browser page. At some point during the viewing by the user of the browser page 150-1 in the browser 140, a navigation command (not specifically shown in the figures) is generated in some manner. Perhaps the user selects a link displayed within the browser page 150-1 in order to navigate to the second browser page 150-2.

In a preferred embodiment of the invention, a navigation command or other mechanism that causes a browser 140 to load or otherwise access another browser page 150 triggers the operation of the state sender logic entity processing shown in Figure 4. Alternatively, an application logic entity 170 itself can complete any required processing of data elements and then can invoke the features of the invention explained here to transfer those data element values to the next browser page.

In any event, in step 300 in Figure 4, operating within a first browser page 150-1, the state sender logic entity 180-2 detects a navigation command (i.e., an intent by either the user or an application logic entity 170) to navigate to a second browser page 150-2.

Next, in step 301, the state sender logic entity 180-2, performing within the browser 140, extracts a value 178 for each data element 175, 176, and so forth shared between the first application logic entity 170-1 and the second application logic entity 172 (contained within the second browser page 150-2, which is not yet loaded into the browser 140) to create a value array 182. A value array 182 in this embodiment is a character delineated array of data element values. Note that there may be a predetermined number of data elements, in which case the state sender logic entity 180-2 may know exactly how many data element values 178 must be appended or placed into the value array, or alternatively, the number of values of data elements that are to be placed into the browser page identifier (being created by this invention) may be dynamically determined, for example, by user input, or by inspecting each data element in a set of data elements to determine how many of the data elements may have values, or via another technique.

For example, as illustrated in Figure 3, the value array 182-1 that the state sender logic entity 180-2 created in step 301 contains the values 178-1 and 178-2 of the data elements 175 and 176, and appears as follows:

ABC&123

In this example, the value array 182-1 represents all of the state information 155 (i.e., contains each of the data element values 178-1, 178-2 in this example) that are to be

passed or transferred from the first browser page 150-1 to the second browser page 150-2 using the techniques of the invention as explained herein. Once the state sender logic entity 180-2 has placed all data element values 178 into a value array 182, processing can proceed to generate a browser page identifier 160 containing the state information 155 (i.e., the value array 182 in this case).

In step 302, the state sender logic entity 180-2 obtains a page descriptor 165-2 for the second browser page 150-2. In this example, the page descriptor 165-2 contains the value:

10 HTTP://COMPUTER/PAGE2.

Next, in step 303, the state sender logic entity 180-2 attends the value array 182-1 containing the values 178 for each data element 175, 176 to the page descriptor 165-2 of the second browser page 150-2 to form a browser page identifier 160-1 for the second browser page 150-2. In other words, in step 303, the state sender logic entity 182 in this example embodiment dynamically creates a URL that references the second browser page 152 and that contains the state information 155 in the form of the value array 182-1 containing the values for data elements 175, 176 that are shared between the application logic entities 170-1 and 170-2. Once the browser page identifier 160-1 for the second browser page 150-1 is constructed in this manner, processing proceeds to step 304.

In step 304, the state sender logic entity 180-2 invokes access to the second browser page 150-2 using the browser page identifier 160-1. In other words, in step 304, the sender state logic entity 180-2 within the first browser page 150-1 causes the browser 140 to retrieve and begin rendering the second browser page 150-2. Invoking the browser page identifier 161 a be performed, for example, by performing an HTTP GET operation to cause the browser 140 to retrieve the browser page 150-2.

In this manner, the state sender logic entity 180-2 captures independence state information 155 to and automatically and dynamically generated browser page identifier 160 in order to transfer the state information to another browser page 150.

Returning attention now to the illustration in Figure 3, in response to the processing just explained with respect to Figure 4, the browser 140 proceeds to retrieve, load and render the second browser page 150-2. Upon doing so, while rendering (i.e., during the loading and displaying of) the second browser page 150-2, the browser 140 encounters the state retrieval logic entity 180-1 configured in accordance with embodiment of the invention, at or near the top of the second browser page 150. At this point in processing, the browser 140 invokes the functionality of the state retrieval logic entity 180-1 within the second browser page 150-2.

Figure 5 illustrates the processing steps of the state retrieval logic entity 180-1 configured in accordance with embodiment of the invention. Generally, the state retrieval logic entity 180-1 is responsible for retrieving any data element values from a browser page identifier 160 which was used to retrieve (i.e., to obtain and load) the browser page 150 in which state retrieval logic entity 181 exists.

To perform such functionality, in step 350, the state retrieval logic entity 180-1 operates in a browser page (e.g., in the second browser page 150-2 in this example) to declare data elements 175,176 for use by one or more application logic entities that may exist within the browser page 150. In this example, step 350, the state retrieval logic entity 181 in the second browser page 150-2 declares (e.g., instantiates or otherwise defines) the data elements 175 and 176.

Next, in step 351, the state retrieval logic entity 180-1 parses the browser page identifier 161 identifying the browser page (i.e., used to invoke the current browser page 150-2) to retrieve a value 178 for a data element 175 (or 176) from the browser page identifier 160-1. In the example illustrated in Figure 3, in step 351, the state retrieval logic entity 180-1 parses the value array 182-1 to obtain, for example, the value 178-1 “ABC” that corresponds to the data element 175-2 “DATA\_ELEMENT\_1.”

Next, in step 352, the state retrieval logic entity 181, while operating within the browser 140, assigns the value 178 (178-1 “ABC” in this example) to a data element 175-2 (in this example) that corresponds to the value 178-1 parsed from the browser page identifier 160-1 (in step 351). In this manner, the system of the invention transfers the data element value 178-1 having a value of “ABC” from the data element 175-1 has used

within the first application logic entity 170-1 in the first browser page 150-1 to the data element 175-2 “DATA\_ELEMENT\_1” (e.g., the JavaScript variable name for the data element 175-2) as will be used by the second application logic entity 170-2 within the second browser page 150-2.

5           Next, in step 353, the state retrieval logic entity determines if other values exist within the browser page identifier that not yet been assigned to a corresponding data element. In this example, the data element value 178-2 “123” still remains to be parsed from the browser page identifier 160-1. Accordingly, another value 178 does exist in the browser page identifier 160 in processing proceeds to step 354.

10           In step 354, the state retrieval logic entity 181 advances to the next value 178-2 in the browser page identifier 160-1 (e.g., moves a pointer to the next value 178-2 in the value array 182-1), after which processing proceeds back to step 351 in order to parse the browser page identifier 161 to obtain the next value 178-2 for assignment (second iteration of step 352) that values corresponding data element 176-2.

15           In step 353, if the state retrieval logic entity 180-1 determines that no further values 178 exist within the browser page identifier 160-1, processing proceeds to step 355 in which point the state retrieval logic entity 180-1 completes its function according to the system of the invention such that data element values 178-1, 178-2 included in the browser page identifier 160-1 for the browser page 150-2 remain assigned to respective  
20           data elements 175-2, 176-2 for access by the second application logic entity 170-2 within the second browser page 150-2. In other words, once the state retrieval logic entity 180-1 extracts and assigns the values 178-1, 178-2 to the data elements 175-2, 176-2 from the browser page identifier 160-1, those data elements 175-2, 176-2 are now accessible (i.e., useable) by an logic entities 170-2, 180-1 and 180-2 within the second browser page 150-  
25           2.

As thus explained, the system of the invention is able to pass state information  
155 such as variable values 178 between logic entities such as JavaScript code within different browser pages 150, without requiring a data structure such as a stack, a heap or permanently allocated memory locations to store such state information 155.

The invention thus allows, for instance as illustrated in the operation of the second application logic entity 170-2 in Figure 3, the application logic entity 170-2 to further modify the initial or original values (i.e., the values obtained from browser page 150-1, as explained above) of the data elements 175-2 and 176-2. In the illustrated example, the second application logic entity 170-2 modifies the initial values “ABC” and “123” of the data elements 175-2 “DATA\_ELEMENT\_1” and 176-2 “DATA\_ELEMENT\_2” via the script statements:

DATA\_ELEMENT\_1 = DATA\_ELEMENT\_1 + “DEF”

DATA\_ELEMENT\_2 = DATA\_ELEMENT\_2 + 1.

As such, the resulting values of the data elements 175-2 “DATA\_ELEMENT\_1” and 176-2 “DATA\_ELEMENT\_2” are “ABCDEF” and “124” (a numerical value), respectively. When the second application logic entity 170-2 completes processing, and the browser 140 again begins processing the state sender logic entity 180-2 (e.g., in response to a navigation command or some other event that requires the browser to load a new page), the state sender logic entity 182 performs as explained above with respect to Figure 4 to produce a browser page identifier 160-2 as illustrated at the bottom of Figure 3. That is, the browser page identifier 160-2 will be as follows:

“HTTP://COMPUTER/PAGE3?ABCDEF&124.”

As illustrated by this example, the values for the data elements 175-2 and 176-2 are thus included in the browser page identifier 160-2, at which point the invention then causes the browser 140 to obtain, load and render another browser page (PAGE3, not specifically shown in this example) which can use the invention to obtain these data element values, as previously explained. This process can repeat from browser page to browser page so that values or other information is passed between such pages (as opposed to being passed first to another executable program such as a server) as needed.

Is to be understood by those skilled in the art that the system of the invention thus provides a mechanism to allow browser pages such as web browser page to include logic entities such as JavaScript, VBScript, any advanced or future form of HTML that might include the capability to include logic instructions, or the like that can send and receive state information 155 to other logic entities in other browser pages. Using this technique then, logic entities in different browser pages can interoperate with each other when web pages are loaded in response to navigation commands or other events in order to form a cohesive software application (i.e., a software application form from a plurality of logic entities interspersed or contained within different browser pages).

Those skilled in the art will understand that there can be many variations made to the operations, techniques and mechanisms explained above while still achieving the same objectives of the invention. Such variations are intended to be covered by the scope of this invention.

As an example, is to be understood by those skilled in the art that state information 155 is not limited to values of data elements used, for example, by script routines embedded within browser pages. Rather, in the context of this invention, state information 155 is intended to include any information, content or data accessible or contained within a browser page which may be captured in intended in any form to a browser page identifier. It is also to be understood that a browser page identifier is not limited to uniform resource locator. Instead, any mechanism for causing a browser to transfer operation to a first browser page in a second browser page may be suitable for use by the invention to include state information 155 in order to transfer the state information 155 from the first browser page to the second browser page. Likewise, it is to be understood that the system of the invention is not limited to implementation in any particular scripting language, browser page development language or environment, or to any particular type of browser. Rather, the invention is meant to be general in nature inapplicable to systems which have poor mechanisms for exchanging information between browser pages.

As another example of such a variation of the aforementioned example descriptions, it is to be understood that the processing steps of the aforementioned

flowcharts may be rearranged will still accomplishing the objectives of the present invention. Those skilled in the art of computer programming will readily understand that there might be many ways to implement a software system that accomplishes the goals of the invention as claimed. As such, the foregoing description of embodiments of the invention are not intended to be limiting. Rather, any limitations to embodiments of the invention are presented in the claims following APPENDIX A.

An example implementation of portions of HTML and JavaScript code comprising an embodiment of the system of the invention are included in APPENDIX A below. Is to be understood this embodiment (i.e., the portions of an implementation shown in APPENDIX A ) is not meant to be limiting of the invention but rather, illustrative of an example use of the techniques to the invention to pass state information from one browser page to another.

The portions of an implementation of the invention shown in APPENDIX A relate to a web page-based system that allows a user to move from page to page to configure a product (the 7750 system, in this example) manufactured by Cisco Systems of San Jose, California, with various features which result in the user being provided with, by the application of the invention within the web pages of this example implementation, a total price of the product as selected for configuration by the user. While APPENDIX A below only shows certain portions of the code and web pages involved in the entire implementation of this system, the entire contents of the code, HTML pages, images, JavaScript, and other logic or data files that comprise the program entitled "Cisco ICS-7750 Configuration Tool" are hereby incorporated by reference in their entirety.



## APPENDIX A

## Notes:

5       The “GetVariables” JavaScript function shown in this APPENDIX below  
corresponds to an example implementation of the state retrieval logic entity 180-1  
discussed above.

      The “sendQueryString” JavaScript function shown in this APPENDIX below  
corresponds to an example implementation of the state sender logic entity 180-2  
discussed above.

10       The HTML Web Pages labeled “step2.html” and “step3.html” are examples of  
browser pages 150 (e.g., 150-1 and 150-2, respectively, in Figure 3) configured in  
accordance with the invention.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000

**“ICS7750.JS”:**

```

5  <!--// Engage Cloaking Device
    var urlString = self.location.href;
    var queryString = urlString.substring(urlString.indexOf('?')+1,
urlString.length)
    var offset,start

10     var
sw,es,rspe,slot,mrp1,mrp2,mrp3,mrp4,mrp5,mrp1a,mrp1b,mrp2a,mrp2b,mrp3a,m
rp3b
    var
mrp4a,mrp4b,mrp5a,mrp5b,dsp1a,dsp1b,dsp2a,dsp2b,dsp3a,dsp3b,dsp4a,dsp4b
15     var
dsp5a,dsp5b,rps,sv1,ups,bat,sv2,c3k,c4k,sv3,sv4,ip1,ip2,sv5,sv6,slot,msl
ot
    var c1a,c1b,c2a,c2b,c3a,c3b,c4a,c4b,c5a,c5b
    var cb1a,cb1b,cb2a,cb2b,cb3a,cb3b,cb4a,cb4b,cb5a,cb5b
20     var str1,str2,str3,str4,str5,str6

function GetVariables(){
    //This function parses the query string and sets the variables
25     offset = 0

    sw = queryString.substring(offset,queryString.indexOf("&",1))
    offset = queryString.indexOf("&",1) + 1

30     es = queryString.substring(offset,queryString.indexOf("&",offset))
    start = queryString.indexOf("&",offset) + 1

    rspe = queryString.substring(start,queryString.indexOf("&",start))
35     offset = queryString.indexOf("&",start) + 1

    mrp1 =
queryString.substring(offset,queryString.indexOf("&",offset))
    start = queryString.indexOf("&",offset) + 1
40     mrp2 = queryString.substring(start,queryString.indexOf("&",start))
    offset = queryString.indexOf("&",start) + 1

    mrp3 =
45     queryString.substring(offset,queryString.indexOf("&",offset))
    start = queryString.indexOf("&",offset) + 1

    mrp4 =
queryString.substring(start,queryString.indexOf("&",start))
50     offset = queryString.indexOf("&",start) + 1

    mrp5 =
queryString.substring(offset,queryString.indexOf("&",offset))
55     start = queryString.indexOf("&",offset) + 1

```

```

        mrp1a =
queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

5         mrp1b =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        mrp2a =
10        queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        mrp2b =
15        queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        mrp3a =
queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

20        mrp3b =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        mrp4a =
25        queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        mrp4b =
30        queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        mrp5a =
35        queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        mrp5b =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

40        dsp1a =
queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        dsp1b =
45        queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        dsp2a =
50        queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        dsp2b =
55        queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

```

```

    dsp3a =
queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1
5
    dsp3b =
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

10
    dsp4a =
queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1

    dsp4b =
15
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

    dsp5a =
20
queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1

    dsp5b =
25
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

    rps = queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1

    sv1 =
30
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

    ups = queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1
35
    bat =
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

40
    sv2 = queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1

    c3k =
45
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

    c4k = queryString.substring(start, queryString.indexOf("&", start))
    offset = queryString.indexOf("&", start) + 1

50
    sv3 =
queryString.substring(offset, queryString.indexOf("&", offset))
    start = queryString.indexOf("&", offset) + 1

    sv4 = queryString.substring(start, queryString.indexOf("&", start))
55
    offset = queryString.indexOf("&", start) + 1

```

```

        ip1 =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1
5
        ip2 = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        sv5 =
10 queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        sv6 = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1
15
        slot =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        ms1ot =
20 queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        cl1a =
25 queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        cl1b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1
30
        c2a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        c2b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1
35
        c3a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1
40
        c3b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        c4a =
45 queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        c4b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1
50
        c5a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1
55

```

```

        c5b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        cb1a =
5    queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        cb1b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1
10
        cb2a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

15        cb2b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

        cb3a =
queryString.substring(offset,queryString.indexOf("&",offset))
20        start = queryString.indexOf("&",offset) + 1

        cb3b = queryString.substring(start,queryString.indexOf("&",start))
        offset = queryString.indexOf("&",start) + 1

25        cb4a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1

        cb4b = queryString.substring(start,queryString.indexOf("&",start))
30        offset = queryString.indexOf("&",start) + 1

        cb5a =
queryString.substring(offset,queryString.indexOf("&",offset))
        start = queryString.indexOf("&",offset) + 1
35
        cb5b = queryString.substring(start,queryString.length)

40
    }//END Function GetVariables

45    <!--//  Engage Cloaking Device

function sendQueryString(handlerURL){

50    str1 = sw + "&" + es + "&" + rspe + "&" + mrp1 + "&" + mrp2 + "&" + mrp3
        + "&" + mrp4 + "&" + mrp5 + "&" + mrp1a + "&" + mrp1b + "&" + mrp2a
        str2 = "&" + mrp2b + "&" + mrp3a + "&" + mrp3b + "&" + mrp4a + "&" +
        mrp4b + "&" + mrp5a + "&" + mrp5b + "&" + dsp1a + "&" + dsp1b + "&" +
        dsp2a

```

```

str3 = "&" + dsp2b + "&" + dsp3a + "&" + dsp3b + "&" + dsp4a + "&" +
dsp4b + "&" + dsp5a + "&" + dsp5b + "&" + rps + "&" + sv1 + "&" + ups +
"&" + bat
str4 = "&" + sv2 + "&" + c3k + "&" + c4k + "&" + sv3 + "&" + sv4 + "&" +
5 ip1 + "&" + ip2 + "&" + sv5 + "&" + sv6 + "&" + slot + "&" + mslot
str5 = "&" + c1a + "&" + c1b + "&" + c2a + "&" + c2b + "&" + c3a + "&" +
c3b+ "&" + c4a+ "&" + c4b+ "&" + c5a + "&" + c5b
str6 = "&" + cb1a + "&" + cb1b + "&" + cb2a + "&" + cb2b + "&" + cb3a +
"&" + cb3b+ "&" + cb4a+ "&" + cb4b+ "&" + cb5a + "&" + cb5b
10 urlBind = handlerURL + "?" + str1 + str2 + str3 + str4 + str5 +
str6;
document.location.href = urlBind;

}

15 function GetQueryString(mrpnum) {

slot = mrpnum
str1 = sw + "&" + es + "&" + rspe + "&" + mrp1 + "&" + mrp2 + "&" + mrp3
20 + "&" + mrp4 + "&" + mrp5 + "&" + mrp1a + "&" + mrp1b + "&" + mrp2a
str2 = "&" + mrp2b + "&" + mrp3a + "&" + mrp3b + "&" + mrp4a + "&" +
mrp4b + "&" + mrp5a + "&" + mrp5b + "&" + dsp1a + "&" + dsp1b + "&" +
dsp2a
str3 = "&" + dsp2b + "&" + dsp3a + "&" + dsp3b + "&" + dsp4a + "&" +
25 dsp4b + "&" + dsp5a + "&" + dsp5b + "&" + rps + "&" + sv1 + "&" + ups +
"&" + bat
str4 = "&" + sv2 + "&" + c3k + "&" + c4k + "&" + sv3 + "&" + sv4 + "&" +
ip1 + "&" + ip2 + "&" + sv5 + "&" + sv6 + "&" + slot + "&" + mslot
str5 = "&" + c1a + "&" + c1b + "&" + c2a + "&" + c2b + "&" + c3a + "&" +
30 c3b+ "&" + c4a+ "&" + c4b+ "&" + c5a + "&" + c5b
str6 = "&" + cb1a + "&" + cb1b + "&" + cb2a + "&" + cb2b + "&" + cb3a +
"&" + cb3b+ "&" + cb4a+ "&" + cb4b+ "&" + cb5a + "&" + cb5b

qs = "?" + str1 + str2 + str3 + str4 + str5 + str6;
35 return qs;

}

40 function buildPartList(){

str1 = sw + "&" + es + "&" + rspe + "&" + mrp1 + "&" + mrp2 + "&" + mrp3
45 + "&" + mrp4 + "&" + mrp5 + "&" + mrp1a + "&" + mrp1b + "&" + mrp2a
str2 = "&" + mrp2b + "&" + mrp3a + "&" + mrp3b + "&" + mrp4a + "&" +
mrp4b + "&" + mrp5a + "&" + mrp5b + "&" + dsp1a + "&" + dsp1b + "&" +
dsp2a
str3 = "&" + dsp2b + "&" + dsp3a + "&" + dsp3b + "&" + dsp4a + "&" +
50 dsp4b + "&" + dsp5a + "&" + dsp5b + "&" + rps + "&" + sv1 + "&" + ups +
"&" + bat
str4 = "&" + sv2 + "&" + c3k + "&" + c4k + "&" + sv3 + "&" + sv4 + "&" +
ip1 + "&" + ip2 + "&" + sv5 + "&" + sv6 + "&" + slot + "&" + mslot
str5 = "&" + c1a + "&" + c1b + "&" + c2a + "&" + c2b + "&" + c3a + "&" +
55 c3b+ "&" + c4a+ "&" + c4b+ "&" + c5a + "&" + c5b

```





**“STEP2.HTML”:**

```

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html xmlns:v="urn:schemas-microsoft-com:vml"
5  xmlns:o="urn:schemas-microsoft-com:office:office"
  xmlns:w="urn:schemas-microsoft-com:office:word"
  xmlns="http://www.w3.org/TR/REC-html40">

<head>
10 <meta http-equiv=Content-Type content="text/html;
   charset=windows-1252">
   <meta name=ProgId content=Word.Document>
   <meta name=Generator content="Microsoft Word 9">
   <meta name=Originator content="Microsoft Word 9">
15 <link rel=File-List href="./step2_files/filelist.xml">
   <link rel=Edit-Time-Data href="./step2_files/editdata.mso">
   <!--[if !mso]>
   <style>
   v\:* {behavior:url(#default#VML);}
20 o\:* {behavior:url(#default#VML);}
   w\:* {behavior:url(#default#VML);}
   .shape {behavior:url(#default#VML);}
   </style>
   <![endif]-->
25 <title>Cisco ICS-7750 Configuration Tool</title>
   <!--[if gte mso 9]><xml>
     <o:DocumentProperties>
       <o:Author>Barry Chapin</o:Author>
       <o:Revision>1</o:Revision>
30 <o:TotalTime>0</o:TotalTime>
       <o:Created>2000-12-01T18:16:00Z</o:Created>
       <o:Pages>1</o:Pages>
       <o:Words>146</o:Words>
       <o:Characters>835</o:Characters>
35 <o:Company>Chapin & Huang, L.L.C.</o:Company>
       <o:Lines>6</o:Lines>
       <o:Paragraphs>1</o:Paragraphs>
       <o:CharactersWithSpaces>1025</o:CharactersWithSpaces>
       <o:Version>9.2720</o:Version>
40 </o:DocumentProperties>
   </xml><![endif]--><!--[if gte mso 9]><xml>
     <w:WordDocument>
       <w:Zoom>0</w:Zoom>
       </w:WordDocument>
45 </xml><![endif]-->
   <style>

```

```

<!--
  /* Style Definitions */
p.MsoNormal, li.MsoNormal, div.MsoNormal
    {mso-style-parent:"";
5      margin:0in;
      margin-bottom:.0001pt;
      mso-pagination:widow-orphan;
      font-size:12.0pt;
      font-family:"Times New Roman";
10     mso-fareast-font-family:"Times New Roman";}
@page Section1
    {size:8.5in 11.0in;
      margin:1.0in 1.25in 1.0in 1.25in;
      mso-header-margin:.5in;
15     mso-footer-margin:.5in;
      mso-paper-source:0;}
div.Section1
    {page:Section1;}
-->
20 </style>

<script language="JavaScript"  src="ics7750.js">

////////////////////////////////////
25  ///
  // Loads the querystring parsing and passing functions
  // used to pass variables and maintain state.
  //////////////////////////////////
  ///
30 </script>

<script language="JavaScript">

<!-- Engage Cloaking Device
35  //////////////////////////////////
  ///
  // Call GetVariables() to load variable from the querystring
  //////////////////////////////////
40  ///

  GetVariables()

  //////////////////////////////////
45  ///
  // popWindow() opens a pop-up window for help/definitions

```

```

////////////////////////////////////
///

function popWindow(link_url)
5  {

    // Creates the pop-up window for definitions and help
    items

10     ContentWindow=window.open(link_url,"ContentWindow","to
    olbar=no,location=no,scrollbars=yes,width=236,height=300,sc
    reenX=25,screenY=25");
    }

15
    //////////////////////////////////////
    ///
    // pageLoad() sets the appropriate graphic in the left
    frame
20    // for the current step and calls buildPartList() to reload
    the
    // right frame parts list.
    //////////////////////////////////////
    ///

25    function pageLoad()
    {

        // Sets status graphic in left-hand frame and call
30    buildPartList()
        // to reload the right-hand frame part list document

        top.leftFrame.document.leftbar.src='images/leftbar_2.g
        if'
35    buildPartList()
    }

    //////////////////////////////////////
    ///
40    // updateVariables() sets variables to the user-selected
    values
    // and sends the querystring to the next page of the
    questionnaire.
    //////////////////////////////////////
45    ///

```

```

function updateVariables(loadPage)
{
    // Sets the sw variable to the value specified by the
5   form

    if(document.swForm.sw[0].checked) {sw = "S77a-1.x.x"}
    if(document.swForm.sw[1].checked) {sw = "S77b-1.x.x"}
    if(document.swForm.sw[2].checked) {sw = "S77c-1.x.x"}
10   if(document.swForm.sw[3].checked) {sw = "S77d-1.x.x"}
    if(document.swForm.sw[4].checked) {sw = "S77e-1.x.x"}
    if(document.swForm.sw[5].checked) {sw = "S77f-1.x.x"}
    sendQueryString(loadPage)
}
15
//--> Disengage Cloaking Device
</script>
<!--[if gte mso 9]><xml>
    <o:shapedefaults v:ext="edit" spidmax="2050"/>
20 </xml><![endif]--><!--[if gte mso 9]><xml>
    <o:shapelayout v:ext="edit">
        <o:idmap v:ext="edit" data="1"/>
    </o:shapelayout></xml><![endif]-->
</head>
25
<body bgcolor=white lang=EN-US link=blue vlink=blue
style='tab-interval:.5in'
marginheight=0 marginwidth=0 leftmargin=0 topmargin=0
onload="pageLoad()">
30
<div class=Section1>

<form name=swForm>

35 <p class=MsoNormal></p>

<table border=0 cellpadding=0 width="100%"
style='width:100.0%;mso-cellspacing:
1.5pt'>
45 <tr>
    <td style='padding:.75pt .75pt .75pt .75pt'>

```

```

    <p class=MsoNormal><b><span style='font-
size:13.5pt'>Select an ICS-7750
    software feature set.</span></b><br>
    <span style='font-size:10.0pt'>The ICS-7750 comes
5    standard with a base
    software set [S77a-1.x.x]. This software resides on the
    <a
    href="javascript:popWindow('def_spe.html')">SPE200</a>
    card and includes the
10    operating system for the SPE200, <a
    href="javascript:popWindow('def_callmanager.html')">Call
    Manager 3.0</a>,
    ICS7750 System Manager and Cisco IOS - IP/VOICE PLUS.
    <br>
15    <br>
    <script language="JavaScript">

    <!-- Engage Cloaking Device

20    // Display the software options displaying the current sw
    value as checked

    document.writeln('<table>')
    document.writeln('<tr>')
25    document.writeln('  <td valign=top colspan=2><font size="-
    1"><b>Standard Software:</b></font></td>')
    document.writeln('</tr>')
    document.writeln('<tr>')
    document.write('      <td valign=top><input type="Radio"
30    name="sw" value="S77a-1.x.x" ')

    if(sw=='S77a-1.x.x') {document.write('checked')}

    document.write('></td>')
35    document.writeln('  <td valign=top><font size="-1">Call
    Manager 3.0, ICS System Manager 1.0 & IOS - IP/VOICE PLUS
    <nobr><b>[S77a-1.x.x]</b></nobr></font></td>')
    document.writeln('</tr>')
    document.writeln('<tr>')
40    document.writeln('  <td valign=top colspan=2><font size="-
    1"><br><b>Optional Upgrades:</b></font></td>')
    document.writeln('</tr>')
    document.writeln('<tr>')
    document.write('      <td valign=top><input type="Radio"
45    name="sw" value="S77b-1.x.x" ')

```

```

if(sw=='S77b-1.x.x') {document.write('checked')}

document.write('></td>')
document.writeln(' <td valign=top><font size="-1">Call
5 Manager 3.0, ICS System Manager 1.0 & IOS - IP/FW/VOICE
PLUS IPsec 56 <nobr><b>[S77b-
1.x.x]</b></nobr></font></td>')
document.writeln('</tr>')
document.writeln('<tr>')
10 document.write(' <td valign=top><input type="Radio"
name="sw" value="S77c-1.x.x" ')

if(sw=='S77c-1.x.x') {document.write('checked')}

15 document.write('></td>')
document.writeln(' <td valign=top><font size="-1">Call
Manager 3.0, ICS System Manager 1.0 & IOS -IP/FW/VOICE PLUS
IPsec 3DES <nobr><b>[S77c-1.x.x]</b></nobr></font></td>')
document.writeln('</tr>')
20 document.writeln('<tr>')
document.write(' <td valign=top><input type="Radio"
name="sw" value="S77d-1.x.x" ')

if(sw=='S77d-1.x.x') {document.write('checked')}
25 document.write('></td>')
document.writeln(' <td valign=top><font size="-1">Call
Manager 3.0, ICS System Manager 1.0 & IOS -
IP/IPX/AT/IBM/VOICE PLUS <nobr><b>[S77d-
30 1.x.x]</b></nobr></font></td>')
document.writeln('</tr>')
document.writeln('<tr>')
document.write(' <td valign=top><input type="Radio"
name="sw" value="S77e-1.x.x" ')
35 if(sw=='S77e-1.x.x') {document.write('checked')}

document.write('></td>')
document.writeln(' <td valign=top><font size="-1">Call
40 Manager 3.0, ICS System Manager 1.0 & IOS -
IP/IPX/AT/IBM/FW/Voice Plus IPsec 56 <nobr><b>[S77e-
1.x.x]</b></nobr></font></td>')
document.writeln('</tr>')
document.writeln('<tr>')
45 document.write(' <td valign=top><input type="Radio"
name="sw" value="S77f-1.x.x" ')

```

```

if (sw=='S77f-1.x.x') {document.write('checked')}

document.write('></td>')
5 document.writeln(' <td valign=top><font size="-1">Call
Manager 3.0, ICS System Manager 1.0 & IOS -
IP/IPX/AT/IBM/FW/VOICE PLUS IPsec 3DES <nobr><b>[S77f-
1.x.x]</b></nobr></font></td>')
document.writeln('</tr>')
10 document.writeln('</table>')

// Disengage Cloaking Device -->
</script></span></p>
</td>
15 </tr>
<tr>
<td style='padding:.75pt .75pt .75pt .75pt'>
<p class=MsoNormal align=right style='text-
align:right'><a
20 href="javascript:updateVariables('stepla.html')"><span
style='text-decoration:
none;text-underline:none'></span></a>
&nbsp;<a
href="javascript:updateVariables('step3.html')"><span
style='text-decoration:
30 none;text-underline:none'></span></a>
35 &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</p>
</td>
</tr>
</table>

40 </form>

</div>

</body>
45 </html>

```

**“STEP3.HTML”:**

```

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html xmlns:v="urn:schemas-microsoft-com:vml"
5  xmlns:o="urn:schemas-microsoft-com:office:office"
  xmlns:w="urn:schemas-microsoft-com:office:word"
  xmlns="http://www.w3.org/TR/REC-html40">

<head>
10 <meta http-equiv=Content-Type content="text/html;
   charset=windows-1252">
   <meta name=ProgId content=Word.Document>
   <meta name=Generator content="Microsoft Word 9">
   <meta name=Originator content="Microsoft Word 9">
15 <link rel=File-List href="./step3_files/filelist.xml">
   <link rel=Edit-Time-Data href="./step3_files/editdata.mso">
   <!--[if !mso]>
   <style>
   v\:* {behavior:url(#default#VML);}
20 o\:* {behavior:url(#default#VML);}
   w\:* {behavior:url(#default#VML);}
   .shape {behavior:url(#default#VML);}
   </style>
   <![endif]-->
25 <title>Cisco ICS-7750 Configuration Tool</title>
   <!--[if gte mso 9]><xml>
     <o:DocumentProperties>
       <o:Author>Barry Chapin</o:Author>
       <o:Revision>1</o:Revision>
30 <o:TotalTime>0</o:TotalTime>
       <o:Created>2000-12-01T18:20:00Z</o:Created>
       <o:Pages>1</o:Pages>
       <o:Words>186</o:Words>
       <o:Characters>1065</o:Characters>
35 <o:Company>Chapin & Huang, L.L.C.</o:Company>
       <o:Lines>8</o:Lines>
       <o:Paragraphs>2</o:Paragraphs>
       <o:CharactersWithSpaces>1307</o:CharactersWithSpaces>
       <o:Version>9.2720</o:Version>
40 </o:DocumentProperties>
   </xml><![endif]--><!--[if gte mso 9]><xml>
     <w:WordDocument>
       <w:Zoom>0</w:Zoom>
       </w:WordDocument>
45 </xml><![endif]-->
   <style>

```



```

<!--
  /* Style Definitions */
p.MsoNormal, li.MsoNormal, div.MsoNormal
    {mso-style-parent:"";
5      margin:0in;
      margin-bottom:.0001pt;
      mso-pagination:widow-orphan;
      font-size:12.0pt;
      font-family:"Times New Roman";
10     mso-fareast-font-family:"Times New Roman";}
@page Section1
    {size:8.5in 11.0in;
      margin:1.0in 1.25in 1.0in 1.25in;
      mso-header-margin:.5in;
15     mso-footer-margin:.5in;
      mso-paper-source:0;}
div.Section1
    {page:Section1;}
-->
20 </style>

<script language="JavaScript"  src="ics7750.js">

////////////////////////////////////
25  ///
  // Loads the querystring parsing and passing functions
  // used to pass variables and maintain state.
  //////////////////////////////////
  ///
30 </script>

<script language="JavaScript">

<!-- Engage Cloaking Device
35  //////////////////////////////////
  ///
  // Call GetVariables() to load variable from the querystring
  //////////////////////////////////
40  ///

  GetVariables()

  //////////////////////////////////
45  ///
  // popWindow() opens a pop-up window for help/definitions

```

```

////////////////////////////////////
///

function popWindow(link_url)
5 {
    ContentWindow=window.open(link_url,"ContentWindow","to
olbar=no,location=no,scrollbars=yes,width=236,height=300,sc
reenX=25,screenY=25");
}
10 //////////////////////////////////////
///
// pageLoad() sets the appropriate graphic in the left
frame
// for the current step and calls buildPartList() to reload
15 the
// right frame parts list.
////////////////////////////////////
///

20 function pageLoad()
{
    // Sets status graphic in left-hand frame and call
buildPartList()
25 // to reload the right-hand frame part list document

    top.leftFrame.document.leftbar.src='images/leftbar_3.g
if'
    buildPartList()
30 }

////////////////////////////////////
///
// updateVariables() sets variables to the user-selected
35 values
// and sends the querystring to the next page of the
questionnaire.
////////////////////////////////////
///

40 function updateVariables(loadPage)
{
    // Sets the sw variable to the value specified by the
45 form

```

```

        if(document.rspeform.rspe[0].checked) {

            if((mrp1=='y') && (mrp2=='y') && (mrp3=='y') && (mrp4=='y') &
5      & (mrp5=='y')) {
                alert("All available slots are full.  You
must remove one or more MRP cards to add the redundant
SPE.")
10      }

                else {rspe = "y"}
                                }
                if(document.rspeform.rspe[1].checked) {rspe = "n"}

15      sendQueryString(loadPage)
    }
    //--> Disengage Cloaking Device
</script>
<!--[if gte mso 9]><xml>
20    <o:shapedefaults v:ext="edit" spidmax="2050"/>
</xml><![endif]--><!--[if gte mso 9]><xml>
    <o:shapelayout v:ext="edit">
        <o:idmap v:ext="edit" data="1"/>
    </o:shapelayout></xml><![endif]-->
25 </head>

<body bgcolor=white lang=EN-US link=blue vlink=blue
style='tab-interval:.5in'
marginheight=0 marginwidth=0 leftmargin=0 topmargin=0
30 onload="pageLoad()">

    <div class=Section1>

    <form name=rspeform>
35
    <p class=MsoNormal></p>

    <table border=0 cellpadding=0 width="100%"
style='width:100.0%;mso-cellspacing:
45    1.5pt'>
        <tr>

```

```

        <td style='padding:.75pt .75pt .75pt .75pt'>
        <p class=MsoNormal><b><span style='font-
size:13.5pt'>Choose Redundant System
Processing Engine (SPE).</span></b><br>
5    <span style='font-size:10.0pt'>The <a
href="javascript:popWindow('def_spe.html')">SPE</a> is a
single-board
computer that can run Cisco <a
10 href="javascript:popWindow('def_callmanager.html')">CallMan
ager</a> and core
voice applications such as voice mail and auto-attendant,
as well as
interactive voice response (IVR), unified messaging,
15 automated call
distributor (ACD), and Web-based contact center
applications. <br>
<br>
The advantages of adding a redundant SPE are increased
20 reliability,
fault-tolerance, and instant fail-over. The disadvantage
is that it takes up
one of the remaining five chassis slots.<br>
<br>
25 </span><b>Would you like to add a redundant SPE?</b><br>
<script language="JavaScript">

// Display the redundant SPE options displaying the current
rspe value as checked
30 document.writeln("<table>")
document.writeln("<tr>")
document.writeln("<td valign=top><input type='Radio'
name='rspe' ")
35 if(rspe=='y') {document.write('checked')}
document.writeln("></td>")

document.writeln("<td valign=top><font size='-
1'>Yes</font></td>")
40 document.writeln("</tr>")
document.writeln("<tr>")
document.writeln("<td valign=top><input type='Radio'
name='rspe' ")
if(rspe=='n') {document.write('checked')}
45 document.writeln("></td>")

```

```

        document.writeln("<td valign=top><font size='-
1'>No</font></td>")
document.writeln("</tr>")

```

```

5  document.writeln("</table>")
    </script></p>
    </td>
    </tr>
    <tr>
10  <td style='padding:.75pt .75pt .75pt .75pt'>
    <p class=MsoNormal align=right style='text-
align:right'><a
    href="javascript:updateVariables('step2.html')"><span
    style='text-decoration:
15  none;text-underline:none'></span></a>
20  &nbsp;<a
    href="javascript:updateVariables('step4.html')"><span
    style='text-decoration:
    none;text-underline:none'></span></a>
    &nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;&nbsp;</p>
    </td>
30  </tr>
    </table>

    </form>

35  </div>

    </body>

    </html>
40  END OF APPENDIX A

```